DATASHEET / BROCHURE

# WorkForce Enterprise AM-C6000



With the smallest footprint in its class, this more sustainable MFP offers the perfect solution for all your business printing needs.

The WorkForce Enterprise AM-C6000 combines fast performance with low energy consumption. Made with the modern office in mind, the small footprint and modular design allow you to build your device to your exact requirements. And as if that wasn't enough, the innovative technology makes installation and maintenance easy and stress free.

## Reliable and improved sustainability

With a simpler, shorter paper path, paper jams can be removed more easily, and the finisher connectivity is improved. This means that service downtimes can be reduced. Through fewer consumables and supplies, it also produces less waste. With low power consumption, the overall environmental impact of printing is cut dramatically.

## Efficient maintenance

Fewer replacement parts keep user intervention to a minimum, making day-today maintenance fast and efficient.

## Heat-Free Technology

Epson Heat-Free Precision Core Technology requires no heat to warm up when it is switched on or awoken from sleep, which significantly reduces energy consumption. This allows Epson's Heat-Free inkjets to deliver an exceptional fast FPOT compared to laser technology.

## Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson Remote Services (ERS), which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

## **KEY FEATURES**

#### High reliability

Simple mechanism for environments where downtime is not an option

- More sustainable Lower power consumption saves energy thanks to Heat-Free technology
- Small footprint Amongst the lowest footprint in its class

• Reduced downtime Simpler, shorter paper path for easier paper jam removal

• Solution compatibility A wide variety of integrated software solutions



# PRODUCT SPECIFICATIONS

TECHNOLOGY			
Printing Method	PrecisionCore™ Micro TFP printhead		
Nozzle Configuration	7,230 Nozzles Black, 7,230 Nozzles per Color		
Minimum Droplet Size	3.8 pl, With Variable-Sized Droplet Technology		
nk Technology	DURABrite™ Pro		
Category	Office Workgroup, Office Departmental		
All-in-One Functions	Print, Scan, Copy		
PRINT			
Number of colours	4 colour		
First Page Out	Monochrome 4.5 Seconds, Colour 4.5 Seconds		
• •	4 60 pages/min Monochrome, 60 pages/min Colour		
Duplex Printing Speed	60 A4 Pages/min Monochrome, 60 A4 Pages/min Colour		
SO/IEC 24734			
Printing Resolution	600 x 2,400 DPI		
Recommended Duty Cycle Colours	8,500 - 60,000 pages per month		
Print from	Black [Pigment], Cyan [Pigment], Yellow [Pigment], Magenta [Pigment] PC, MAC, Cloud, Direct USB, Mobile Device (WiFi Direct)		
SCAN			
Double-sided scanning	Yes		
Scanning Speed	60 ipm (Monochrome, Single-sided, ADF) * Scanning in accordance with ISO/IEC 17991; 60		
	ipm ( Colour, Single-sided, ADF ) * Scanning in accordance with ISO/IEC 17991; 120 ipm (		
	Monochrome, Double-sided, ADF) * Scanning in accordance with ISO/IEC 17991; 120 ipm (		
	Colour, Double-sided, ADF) * Scanning in accordance with ISO/IEC 17991; 0.4 msec/line (		
Optical Resolution	Colour, 300 dpi, Flatbed ); 0.6 msec/line ( Colour, 600 dpi, Flatbed ); 600 DPI x 1,200 DPI (Horizontal x Vertical)		
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)		
Advanced document	Scan to Email, Scan to FTP, Scan to Network folders, Scan to USB, Computer (Epson		
ntegration	Document Capture Pro)		
Maximum scan size	297 mm x 431 mm		
Output formats	BMP, JPEG, TIFF, multi-TIFF, PDF, searchable PDF, PDF/A, PNG, Secured PDF		
Scanner type	Contact image sensor (CIS)		
FAX			
Type of fax	Walk-up black and white and colour fax capability		
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page		
ax speed dials (max)	2,000 names and numbers		
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)		
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Speed Dial, Fax to Folder, Address		
	Book, Fax Preview, Polling Reception		
COPY			
Copy resolution (dpi)	600 × 600		
Reduction / Enlargement	25 % - 400 %		
Maximum number of copies	2,000		
Maximum Copy Size	A3		
CONNECTIVITY			
Network Printing Protocols	LPR, FTP, IPP, LPD, Port 2501, Port 9100, WSD, IPSec, WSD-Print, IPPS, IS, Bonjour/Airprint,		
Network Frinting Frotocols			
Ū	SMB 1.0, SMB 2.0, SMB 3.0 SMMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP,		
Vetwork Management	SMB 1.0, SMB 2.0, SMB 3.0		
Network Management	SMB 1.0, SMB 2.0, SMB 3.0 SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP,		
Vetwork Management Protocols	SMB 1.0, SMB 2.0, SMB 3.0 SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP, LLMNR, POP3, IPSec, IEEE 802.1X, ARP, GARP, EAP, ICMP, IGMP, DNS-SD, HTTPS, XMPP, SMTPS, LDAP, LDAPS, SNMP 1.0, SNMP 2.0c, SNMP 3.0, SNMP Trap		
Network Management Protocols Network Scanning Protocols Interfaces	SMB 1.0, SMB 2.0, SMB 3.0 SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP, LLMNR, POP3, IPSec, IEEE 802.1X, ARP, GARP, EAP, ICMP, IGMP, DNS-SD, HTTPS, XMPP, SMTPS, LDAP, LDAPS, SNMP 1.0, SNMP 2.0c, SNMP 3.0, SNMP Trap		
Vetwork Management Protocols Network Scanning Protocols	SMB 1.0, SMB 2.0, SMB 3.0 SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP, LLMNR, POP3, IPSec, IEEE 802.1X, ARP, GARP, EAP, ICMP, IGMP, DNS-SD, HTTPS, XMPP, SMTPS, LDAP, LDAPS, SNMP 1.0, SNMP 2.0c, SNMP 3.0, SNMP Trap WSD-Scan, FTP, SMB 1.0, SMB 2.0, SMB 3.0		
Vetwork Management Protocols Network Scanning Protocols	SMB 1.0, SMB 2.0, SMB 3.0 SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP, LLMNR, POP3, IPSec, IEEE 802.1X, ARP, GARP, EAP, ICMP, IGMP, DNS-SD, HTTPS, XMPP, SMTPS, LDAP, LDAPS, SNMP 1.0, SNMP 2.0c, SNMP 3.0, SNMP Trap WSD-Scan, FTP, SMB 1.0, SMB 2.0, SMB 3.0 Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), USB 2.0-A, Wireless LAN IEEE		
Vetwork Management Protocols Vetwork Scanning Protocols	SMB 1.0, SMB 2.0, SMB 3.0 SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SMTP, LLMNR, POP3, IPSec, IEEE 802.1X, ARP, GARP, EAP, ICMP, IGMP, DNS-SD, HTTPS, XMPP, SMTPS, LDAP, LDAPS, SNMP 1.0, SNMP 2.0c, SNMP 3.0, SNMP Trap WSD-Scan, FTP, SMB 1.0, SMB 2.0, SMB 3.0 Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), USB 2.0-A, Wireless LAN IEEE 802.11a/b/g/n/ac (optional), USB 3.2 Gen 1x1		

## WorkForce Enterprise AM-C6000

## WHAT'S IN THE BOX

- Information sheet
- Power cable
- User guide
- Initialization Ink Supply Units



# PRODUCT SPECIFICATIONS

## WorkForce Enterprise AM-C6000

PAPER / MEDIA HANDLING	
Paper Formats	A3 (29.7x42.0 cm), A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), B6, B5, B4, Letter, Executive, C5
i apoi i oimato	(Envelope), User defined
Automatic Document Feed	150 pages
Compatible Paper Weight	52 g/m <sup>2</sup> - 300 g/m <sup>2</sup>
Duplex	Yes (A4/A3, plain paper)
Output Tray Capacity	500 Sheets
Paper Tray Capacity	1,150 Sheets Standard, 5,150 Sheets Maximum
Standard paper tray(s)	2 x 500-Sheet paper tray
Optional paper tray(s)	2 x 500-Sheet paper tray, Cabinet
Maximum paper input	5,150
Number of paper trays	2
· · · · • • • • • • • • • • • • • • • •	
PAPER FEED MPT	
Paper Input Name	MPT
Paper Formats	A3, A4, A5, B4, B5, B6, Letter, EXE
Custom sizes	Min 55x 140 mm to Max 297x 1,200 mm
Compatible paper weight	52 g/m² - 300 g/m²
Paper Capacity 1	150 Sheets of Plain Paper
	-
Paper Capacity 2	10 Envelopes
PAPER FEED C1	
Paper Input Name	C1
Paper Formats	A3, A4, A5, B4, B5, Letter
Custom sizes	Min 85x 140 mm to Max 297x 431.8 mm
Compatible paper weight	52 g/m <sup>2</sup> - 300 g/m <sup>2</sup>
Paper Capacity 1	500 Sheets of Plain Paper
Paper Capacity 2	150 Postcards
PAPER FEED C2-C4	
Paper Input Name	C2-C4
Paper Formats	A3, A4, A5, B4, B5, Letter
Custom sizes	Min 85x 140 mm to Max 297x 431.8 mm
Compatible paper weight	52 g/m² - 300 g/m²
Paper Capacity 1	500 Sheets of Plain Paper
Paper Capacity 2	150 Postcards
PAPER FEED DUPLEX	
	Dupley
Paper Input Name	Duplex
Custom sizes	Min 139.7x 182 mm to Max 297x 431.8 mm
Compatible paper weight	52 g/m² - 250 g/m²
PAPER FEED LCT	
Paper Input Name	LCT
Paper Formats	A4, B5, Letter
-	
Compatible paper weight	60 g/m <sup>2</sup> - 160 g/m <sup>2</sup>
Paper Capacity 1	3,000 Sheets of Plain Paper
GENERAL	
Energy Use	115 Watt (standalone copying, ISO/IEC 24712 pattern), 1 Watt (sleep mode), 46 Watt (Ready),
	0.1 Watt (Power off), TEC 0.25 kWh/week
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	555 x 620 x 1,214 mm (Width x Depth x Height)
Product weight	124.3 kg
Compatible Operating	Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.9.5 or later, Windows
Systems	10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows
	Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows
	Server 2012 R2, Windows Server 2016, macOS 11 or later
Sound Power	Operation: 7.2 B (A)
Noise	Operation: 57 dB (A)
Mobile and Cloud printing	Apple AirPrint, Mopria, Epson Smart Panel App, Epson Connect (Email Print, Remote Print
services	Driver)
Power supply	100V, 220V, 240V
Optional extras	Hard Drive, Cover Plus warranty extensions, Wi-Fi unit



# PRODUCT SPECIFICATIONS

ADDITIONAL FEATURES		
Memory	8,192 MB	
Features Touchscreen, Direct Print, Direct print from USB, Nozzle Verification Technology		
Panel	Type: Color, Touchscreen, Diagonal: 25.7 cm	
Security Functions	Limit access function with Epson Web Config, Secure confidential printing with PIN code	
	release, IEEE802.1x, Panel Admin Mode	
HDD	320 GB Encrypted AES-256	
OTHER FEATURES		
Emulations	PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour	
Optional Software & Solu	tions Epson Device Admin, Epson Net Config, Epson Print Admin, Epson Print Admin Serverless	
Security	TLS, TLS V1.1, TLS V1.2, TLS V1.3, SSL, SNMP V3, IPSec, Document Encryption, Data storage	
	Encryption, WPA2, WPA3, PIN code Release, Panel Admin Mode	



#### SUPPLIES

- Maintenance Box (AM-C4000/5000/6000)
- WorkForce Enterprise AM-C5000/6000 Black Ink
- WorkForce Enterprise AM-C5000/6000 Cyan Ink
- WorkForce Enterprise AM-C5000/6000 Magenta Ink
- WorkForce Enterprise AM-C5000/6000 Yellow Ink

## **OPTIONAL ACCESSORIES**

- Authentication Device Table-P1 C12C937381
- EpsonNet 10/100/1000Base Tx Int C12C934471
- Expansion Board-P1 (OCR unit) C12C936801
- HDD-P1
- C12C936791 • Super G3/G3 Fax Board
- C12C934491 • Wireless LAN Interface-P1 (5GHz) C12C936861


## LOGISTICS INFORMATION

ѕки	C11CJ91401BY
EAN code	8715946705712
Country of Origin	Indonesia

```
C12C937181
C13T08G100 50,000 pages
C13T08G200 30,000 pages
C13T08G300 30,000 pages
C13T08G400 30,000 pages
```



## INK YIELD DATA



\* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

1. - Approx. page yield with the AM C6000. Actual yield will vary depending on images printed and usage conditions. For more information visit

www.epson.eu/pageyield. 2. - Fax optional in certain territories at an additional

cost. Please contact your local Epson office for more information.

 Approx. based on internal testing; may vary depending on the number of copies selected, the output environment, as well as the settings for size, orientation, position of paper.
 Wireless optional in certain territories at an

 Wireless optional in certain territories at an additional cost. Please contact your local Epson office for

more information. 5. -Power consumption based on main body and dual

cassette

**EPSON**<sup>®</sup>

For more information please contact:

Home users: 0343 90 37766 Business users<sup>1</sup>: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus \* 10p per minute plus network extras. Web: www.epson.co.uk www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2023-01-05